

HALCOR

COPPER TUBES
TALOS[®]
PLATED[™]





Product Description

TALOS PLATED™ copper tubes have been developed for use in plumbing and surface heating installations. These metal-plated copper tubes provide unique aesthetics and are suitable for both new-build and renovation work. There is no need to conceal the tubes and the result delivers a smart finish, which is easy to keep clean. TALOS PLATED™ copper tubes possess excellent resistance to internal, as well as, external corrosion due to the inherent properties of copper and the tough external coating. The metallic coating ensures a brightly polished, mirror-like surface that is long lasting and is well matched with other plated accessories found in contemporary bathroom and heating installations. TALOS PLATED™ copper tubes are supplied in half-hard or soft temper that enables easy bending. This makes TALOS PLATED™ copper tubes quick to install, saving time and money.

TALOS PLATED™ Copper Tube Half Hard in Straight Lengths

Outside Diameter * (mm)	Wall Thickness (mm)	Length ** (m)
10	0,80	2 / 2,75 / 3
12	1,00	2 / 2,75 / 3
15	0,70	2 / 2,75 / 3
15	1,00	2 / 2,75 / 3
18	1,00	2 / 2,75 / 3
22	0,90	2 / 2,75 / 3
22	1,00	2 / 2,75 / 3

* Additional diameters and tempers are available upon request.

** Additional lengths are available upon request.

Product Features

- Long lasting plated surface for that modern chromium-look which fits perfectly with contemporary taps, radiators, towel rails and bathroom fittings.
- Suitable for all exposed plumbing and heating installations, in both horizontal and vertical runs.
- Half-hard temper to retain the bendable qualities of copper tube.
- Supplied in a variety of straight lengths to save waste.

Material

Copper phosphorus deoxidised (DHP-Cu) with min. copper content 99.9% and P=0.015% - 0.040%.

Specifications:

Mechanical properties: EN1057

Internal cleanliness: EN1057

Company standard: TB010

